



CMCP140/150 NEMA 4 and 4X Enclosures

CMCP140 / 150 DIN Rail mount Driver, or Proximitor® Enclosures are offered in NEMA 4 and NEMA 4X. Not restricted to Eddy Probe Drivers, other interface devices such as transmitters may be mounted in them. DIN Rail mounted terminal strips for the intermediate termination of Accelerometers, RTD's, TC's, and other sensors are available.



The enclosure cover has a continuous hinge on the long side of the unit, and is secured to the box with clamps. All enclosures are provided with an oil resistant gasket and stainless steel clamps for easy access.

All enclosures may be air purged with plant air to meet the needs of hazardous areas. A simple purge fitting connection is available as a standard option. Hazardous area air purge systems can be supplied by STI upon request.

NEMA 4 Enclosures are ANSI 61 Powder paint (gray) coated on the all surfaces, and are constructed from 14 gauge mild steel.

NEMA 4X Enclosures are constructed from 14 gauge 304 Stainless Steel, and will better resist corrosive environments.

-XX	Enclosure Dimensions:
-01 thru -04	10.0" H x 8.0" W x 6.0" D (25.4 x 20.3 x 15.2 cm)
-05 thru -06	12.0" H x 10.0" W x 6.0" D (30.5 x 20.3 x 15.2 cm)
08	14.0" H x 12.0" W x 6.0" D (35.6 x 30.5 x 15.2 cm)
10	16.0" H x 14.0" W x 6.0" D (40.6 x 35.6 x 15.2 cm)
14	20.0" H x 16.0" W x 10.0" D (50.8 x 40.6 x 25.4 cm)

Ordering Information:

CMCP140	-XX	-XX	NEMA 4 Enclosure:
	-01 thru -04		1-4 Drivers
	-05 thru -06		5-6 Drivers
	08		8 Drivers
	10		10 Drivers
	14		14 Drivers
		00	No Purge
		01	Simple Purge
		XX	X,Y, or Z Purge

CMCP150	-XX	-XX	NEMA 4X Enclosure:
	-01 thru -04		1-4 Drivers
	-05 thru -06		5-6 Drivers
	08		8 Drivers
	10		10 Drivers
	14		14 Drivers
		00	No Purge
		01	Simple Purge
		XX	X,Y, or Z Purge